

RUIDE

RX 52

TOTAL STATION



The High Performance
Total Station with Great
Reliability, Flexibility and Economy

SPECIFICATIONS

RX 52	
Measuring Range	
1P	5.0km
3P	8-10 km
Non prism	1000m
Digital Display	Maximum: 99999999.9999 Minimum: 0.1mm
Accuracy	With prism: 2mm+2ppm, without prism 3mm+2ppm
Measuring Time	Tracking 0.1s, Fine 0.3s (optimal)
Atmospheric Correction	Automatic Correction by Inputting Parameter
Prism Constant	Automatic Correction by Inputting Parameter
Angle Measurement	
Measurement Method	Absolute Encoding
Diameter of The Raster Disk	79mm
Minimum Reading	1 " / 5 " Optional
Accuracy	2 "
Detection Method	Horizontal: Four Sensors Vertical: Four Sensors
Telescope	
Image	Erect
Length	154mm
Effective Aperture	45mm (DTM 50mm)
Magnification	30 X
Field of View	1° 30'
Resolving Power	3 "
Minimum Focus	1m
Compensation	
System	Dual axis liquid-electric
Working Range	± 3'
Resolving Power	1 "
Sensitivity of Vials	
Plate Vial	30 " /2mm
Circular Vial	8' /2mm
Laser Plummet	Yes
Data Storage and Communication	
Internal Memory	120000 points
External Memory	SD card (up to 32G)
Communication Port	RS-232, mini USB
Display	
Type	Dual sides, 6 lines, black and white
Battery	
Power Supply	Rechargeable battery (3100mAH)
Voltage	7.4V DC
Operation Time	20 hours
Dimension and Weight	
Dimension	160mm×150mm×330mm
Weight	5.7 kg
Environmental Specification	
Dust/Water (IEC60529)	IP66
Working Temperature Range	-20℃~50℃
Humidity	95%, non-condensing



NS TECHNOLOGY & CONSULTANT

Registered Office: Mahavir Enclave Part-1 , New Delhi -110045,
Corporate Office: Office No. B3, Plot H7, Aggarwal Plaza, Netaji Subhash Place, New Delhi-110034
Tel.: 011-41005275, **Mob.:** +91-9911283856 , 8700192050,
Email : pssharmapankajk2@gmail.com
Website : www.nstechconsultant.com